



MILLENNIUM SERIES H250B SPEC SHEET

NOMINAL OUTPUT POWER:

Output power is 250 amps DC at 28 VDC continuous, 1000 amps starting current at 24 VDC.

INPUT POWER REQUIREMENTS:

Input requirements 208-240VAC Single Phase at 70 amps.

STANDARD FEATURES:

The Foxcart is enclosed in an all steel chassis with flip-up cover for easy maintenance. Maneuvering is easy with the three inflatable tires and Tow Bar. The unit includes one (1) internal sealed lead acid Aircraft Battery, with option for 2nd battery available, that assists during starts over 250 Amps. Easy to view controls and display consist of DC Volt and DC Amp Meter, DC Power Switch, Battery Test Switch and Power to Aircraft "ON" Annunciation. A 75 Ft 8/3 AC cable with a Hubbel connector and a 15 Ft. 2/0 DC output cable with an Anderson Aircraft Connector is also provided in the standard configuration.

PHYSICAL DIMENSIONS:

Width:	37.00"	Length	49.00"
Height:	21.50"	Weight	500 lbs.

WARRANTY:

Foxtronics warrants each new Foxcart to be free of defects in material and workmanship, under normal use and service, for a period of three (3) years from date of shipment. Internal battery One (1) year from date of shipment. **EXCEPTION: The Manufacture's Warranty supersedes any and all other warranties of Aircraft Batteries supplied by Foxtronics to be operated in the Millennium series Foxcarts.**

